

# PAINT STRIPPER K



Product for paint, membrane and foam removal

## DESCRIPTION AND APPLICATIONS

Concentrated stripping product, highly effective for removal and cleaning of old coatings, waterproofing membranes, insulating foam residues.

High softening performance for a wide range of synthetic resins (polyurethane, acrylics, etc) improving cleaning and support preparation task, as a previous step for a refurbishment job (flooring, waterproofing).

- Also useful for oil stains treatments.
- Methylene chloride-free
- Water dilutable, water rinsable.

## TECHNICAL DATA

### PRODUCT DATA

|                             |                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------|
| <b>Chemical description</b> | Active solvent mixture with thickening and tensioactive agents.                              |
| <b>Physical state</b>       | Semi-liquid                                                                                  |
| <b>Packaging</b>            | Metal container<br>4 kg                                                                      |
| <b>Flash Point</b>          | 10°C                                                                                         |
| <b>Colour</b>               | Whitish                                                                                      |
| <b>Density</b>              | 1.17 g/cm <sup>3</sup> (20°C)                                                                |
| <b>VOC content</b>          | 948 g/L, 90%                                                                                 |
| <b>Storage</b>              | Keep indoor, in a dry and ventilated place, in its unopened original container, at 5°C-35°C. |
| <b>Use before</b>           | 12 months after manufacturing date.                                                          |

## MIXING

Stir gently before use.

## USE CONDITIONS

Substrate temperature must be above 5°C and be 3°C above the current dew point.

## APPLICACIÓN

Spread a thick layer by brush. Leave for 30 minutes. If necessary, apply a second coat. Remove softened coating with a spatula and rinse finally the treated surface with water

## TOOL CLEANING

Clean contaminated tools with water.

## SAFETY

Paint Stripper K contains dangerous substances. Always follow instructions as stated in the Material Safety Data Sheet.

## ENVIRONMENTAL PRECAUTIONS

Empty containers must be handled taking the same precautions as if they were full. Containers must be considered as hazardous waste, to be transferred to an authorized waste manager

## OTHER INFORMATION

The information contained in this Data Sheet, as well as our advice, both written as verbal or provided through testing, are based on our experience, and they do not constitute any product guarantee for the installer, who must consider them as simple information.

We recommend to study deeply all information provided before proceeding to the use or application of any of our products, and strongly advise to conduct tests "on-site" in order to determine their convenience for a specific project.

Our recommendations do not exempt of the obligation of installers to deeply study the right application method for these systems before use, as well as to conduct as many preliminary tests as possible should any doubt arise. The application, use and processing of our products are beyond our control, and therefore under the exclusive responsibility of the installer. In consequence, the installer will be the only responsible of any damage derived from the partial or total in-observation of our indications, and in general, of the inappropriate use or application of these materials.

***This Data Sheet supersedes previous versions.***

