

## Recycled rubber crumb sheet

### DESCRIPTION

Rubber Mat and Rubber Mat Plus are sheets of recycled rubber crumb bonded with a polyurethane resin. They make an excellent buffer base for impact absorption, especially in sport flooring. Certified to EN14904.

They are used in the Pavisoft Sport System, suitable for:

- Hospitals
- Gyms
- Schools
- Commercial areas
- Offices
- Showrooms
- Multi-purpose recreational areas.

### TECHNICAL DATA

INFORMATION ON THE PRODUCT BEFORE APPLICATION				
	Rubber Mat		Rubber Mat Plus	
<b>Chemical description</b>	SBR rubber agglomerate		SBR rubber agglomerate	
<b>Colour</b>	Black		Black	
<b>Hardness (shore)</b>	55A		45A	
<b>Density</b>	0,8 g/cm <sup>3</sup>		0,6 g/cm <sup>3</sup>	
<b>Packaging</b>	1.5 m width rolls Roll weight: 144 to 151 kg each		1.5 m width rolls Roll weight: 108 to 113 kg each	
	<b>Thickness (mm)</b>	<b>Length (m)</b>	<b>Thickness (mm)</b>	<b>Length (m)</b>
	4	30	4	30
	5	24	5	24
	6	20	6	20
	7	17	7	17
	8	15	8	15
	9	14	9	14
	10	12	10	12
<b>Storage</b>	Keep at temperatures below 35°C, away from sunlight. Avoid contact with oils, solvents, petrol or related products.			
<b>Use before</b>	Use before 24 months after manufacturing date.			

### APPLICATION INFORMATION

Please refer to the Pavisoft Sport System information for specific guidance.

### SAFETY

Always consult information provided in the Safety Data Sheet of this product.

### OTHER INFORMATION

The information contained in this DATA SHEET, as well as our advice, both written as verbal or provided through testing, are based on our experience, and they do not constitute any product guarantee for the installer, who must consider them as simple information.

We recommend to study deeply all information provided before proceeding to the use or application of any of our products, and strongly advise to conduct tests "on-site" to determine their convenience for a specific project.

Our recommendations do not exempt of the obligation of installers to deeply study the right application method for these systems before use, as well as to conduct as many preliminary tests as possible should any doubt arise. The application, use and processing of our products are beyond our control, and therefore under the exclusive responsibility of the installer. In consequence, the installer will be the only responsible of any damage derived from the partial or total in-observation of our indications, and in general, of the inappropriate use or application of these materials.

**This data sheet supersedes previous versions.**